

FUEL MAX SSD AND SST WITH DURASEAL

WIDE-BASE TIRES FOR ENHANCED FUEL EFFICIENCY AND LONG MILES TO REMOVAL

Fuel Max® Technology helps lower fuel costs while new tread designs promote even wear and long miles to removal. Built-in DuraSeal Technology® helps seal punctures to keep trucks rolling.* Plus, these Goodyear® wide-base singles enable fleets to maximize payload with significant weight savings over standard dual-tire configurations.

*Seals up to 1/4" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.



SmartWay® Verified

Fuel Max SSD





FUEL MAX SSD AND SST WITH DURASEAL™ WIDE-BASE TIRES FOR ENHANCED FUEL EFFICIENCY AND LONG MILES TO REMOVAL



FUEL MAX SSD

WIDE-BASE DRIVE TIRE FOR ENHANCED FUEL EFFICIENCY AND LONG MILES TO REMOVAL

- SPECIAL TREAD COMPOUND for enhanced fuel economy
- OPTIMIZED TREAD DESIGN AND TIRE FOOTPRINT for even wear and long miles to removal
- TREDLOCK® TECHNOLOGY with interlocking microgrooves helps stabilize the tread for high mileage
- WIDE GROOVES WITH STONE EJECTORS resist stone drilling and enhance casing life
- OPEN SHOULDER DESIGN for all-season traction
- BUILT-IN DURASEAL TECHNOLOGY® helps seal tread punctures* and reduce downtime



The Fuel Max SSD is available in the following size and load range:

Tire Size	Load	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Overall Width Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth			Speed Rating	
	Range	lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	naully	launy
445/50R22.5	L	10,200	4,625	120	830	N/A	N/A	N/A	N/A	190	86.3	14	17.4	442	40	1016	18.5	470	522	324	24	N/A	N/A	75	

^{*}Seals up to ¼" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures



FUEL MAX SST

WIDE-BASE TRAILER TIRE WITH ENHANCED FUEL EFFICIENCY

- SPECIAL TREAD COMPOUND for enhanced fuel economy
- OPTIMIZED TREAD DESIGN AND TIRE FOOTPRINT promote even wear and long miles to removal
- BUILT-IN DURASEAL TECHNOLOGY helps seal tread punctures* and reduce downtime



The Fuel Max SST is available in the following size and load range:

	Tire Size	Load Range	Single Load			Single Inflation		Load	Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPK	Tread Depth		Dual cing	Speed
			lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	Rating
- [445/50R22.5	L	10.200	4.625	120	830	N/A	N/A	N/A	N/A	167.24	75.85	14	17.5	445	39.2	996	18.1	460	526	327	12	N/A	N/A	75

^{*}Seals up to ¼" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures

Talk to a Goodyear® representative to learn more about how Fuel Max SSD and Fuel Max SST tires can help your fleet save money.











Find your total solution at goodyeartrucktires.com.

*Fleet research study, Nov. 2015, Lieberman Research Worldwide. 590-fleet sample. Goodyear Dealer network roadside service compared to Michelin, Bridgestone and Continental.

